

# WARRENDER, LTD.

This chart shows the proper components required for ordering **WARRENDER "WMCH"** series standard Thermoplastic Centrifugal Pumps.

To order simply:  
Select the series and size pump you need from the brochures and performance curves.  
Then select one option from each of the 5 categories shown in the column below and write its code after the series & size designation.

## CATEGORY SELECTION:

### SERIES:

**WMCH** Standard Thermoplastic Centrifugal Pumps.

### SIZE:

11000  
16000  
28000  
51000  
81000  
91000

### MATERIAL:

**P** - Polypropylene  
**V** - PVDF ( Kynar )  
**F** - PVF ( Polypropylene Head / PVDF Internals )

### MAGNETIC COUPLING:

**2** - Standard Neodymium  
**3** - Internal Neodymium / External CS

### PORTS:

**T** - FNPT Threaded  
**F** - ANSI 150# Flanges  
**H** - \* Hose Barbs

### MOTOR DRIVE:

<b>1</b> - TEFC, Close-Coupled, 3 phase	<b>4</b> - * UL-EXP, Close-Coupled, 1 phase
<b>2</b> - * TEFC, Closed-Coupled, 1 phase	<b>5</b> - Bearing Pedestal for Base Mounting
<b>3</b> - UL-EXP, Close-Coupled, 3 phase	<b>6</b> - Complete Close Coupled pump, less motor

\* Available on Models WMCH 11001 thru WMCH 16003 **ONLY**  
150# ANSI Flanged Ports are standard on Models WMCH 28000 and Larger  
For Specific Materials of Construction Refer to Production Code Sheet.

ORDERING EXAMPLE  
**WMCH 28001 P 2 F 1**

