

# WARRENDER, LTD.

This chart shows the proper components required for ordering "**WMP**" series standard Thermoplastic Sliding Vane Pumps.

To order simply:  
Select the series and size pump you need from the brochures and performance curves.  
Then select one option from each of the 5 categories shown in the column below and write its code after the series & size designation.

## CATEGORY SELECTION:

### SERIES:

**WMP** Standard Thermoplastic Sliding Vane Pumps.

### SIZE:

114  
214  
314  
414

### MATERIAL:

P - Polypropylene  
V - PVDF ( Kynar )

### MAGNETIC COUPLING:

1 - Ferrite  
2 - Samarium Cobalt

### MOTOR DRIVE:

1 - TEFC, Close-Coupled, 3 phase  
2 - TEFC, Close-Coupled, 1 phase  
3 - UL-EXP, Close-Couple, 3 phase  
4 - UL-EXP, Close-Couple, 1 phase  
5 - Bearing Pedestal for Base Mounting  
6 - Complete Close Coupled pump, less motor

All pumps are provided with NPT **THREADED PORTS** and NEMA 56C Closed-Coupled motors **STANDARD**

For Specific Materials of Construction Refer to Production Code Sheet.

## ORDERING EXAMPLE

**WMP 114 P 2 T 1**

