

# WARRENDER, LTD.

This chart shows the proper components required for ordering WARRENDER "WMPA P.D." series standard alloy Vane Mag Drive pumps.

## CATEGORY SELECTION:

To order simply:

Select the series and size pump you need from the brochures and performance curves.

Then select one option from each of the 5 categories shown in the column below and write its code after the series & size designation.

## SERIES:

**WMPA** Standard Alloy Rotary Vane Mag-drive

## SIZE:

114  
214  
314  
414  
614  
814  
1014  
1514  
2014

## MATERIAL:

I - Incoloy 825  
H - Hastelloy C276  
S - Stainless Steel

## MAGNETIC COUPLING:

2 - Samarium Cobalt

## PORTS

T= NPT Threaded  
F= ANSI 150# Flanged

## MOTOR DRIVE:

1 - TEFC, Close-Coupled, 3 phase  
2 - TEFC, Close-Coupled, 1 phase  
3 - UL-EXP, Close-Couple, 3 phase  
4 - UL-EXP, Close-Couple, 1 phase  
5 - Bearing Pedestal for Base Mounting  
6 - Complete Close Coupled pump, less motor

For Specific Materials of Construction Refer to Production Code Sheet.

## ORDERING EXAMPLE

**WMPA 114 S 2 T 1**

