

WARRENDER, LTD.

SERIES "WMT" SELECTION CHART

This chart shows the proper components required for ordering "WMT" series standard Thermoplastic Regenerative Turbine Pumps.

To order simply:
Select the series and size pump you need from the brochures and performance curves.
Then select one option from each of the 6 categories shown in the column below and write its code after the series & size designation.

CATEGORY SELECTION:

SERIES:

WMT Thermoplastic Regenerative Turbine Pumps.

SIZE:

3003
5002
5003
7002
7003
9002
9003
12002
16002

MATERIAL:

P- Polypropylene
V- PVDF (Kynar)
F- PVF (Polypropylene Head / PVDF Internals)

MAGNETIC COUPLING:

1- Ferrite (**DISCONTINUED**)
2- Samarium Cobalt
3- Dual CS

PORTS:

T- FNPT Threaded
F- ANSI 150# Flanges
H- * Hose Barbs

MOTOR DRIVE:

1- TEFC, Close-Coupled, 3 phase
2- * TEFC, Closed-Coupled, 1 phase
3- UL-EXP, Close-Coupled, 3 phase
4- * UL-EXP, Close-Coupled, 1 phase
5- Bearing Pedestal for Base Mounting
6- Complete Close Coupled pump, less motor

* Available on Models WMT3003 thru WMT7002 **ONLY**
For Specific Materials of Construction Refer to Production Code Sheet.

ORDERING EXAMPLE
WMT 7003 P 2 F 1

